JP05-25-06 09:25:56 p



FIG. 1



FIG. 2

Smoothness of movement	30	15	10
Image activity	1	3	5


(a)
fa
fb
fc
fd
(b)
fa
fd
fb
ma
md
mb

FIG. 3


254
251
252
253
Encoding parameter generator
Amount of coded bits predicting device
Encoding parameter corrector
25
250
26

FIG. 4



FIG. 5A



FIG. 5B

EP 0 805 452 A2

Case in which almost no motion verctor is present



FIG. 6A

Case in which motion vectors in the same direction/size are distributed over the entire frame



FIG. 6B

Case in which a motion vector partially located in frame



FIG. 6C

Case in which motion vectors are distributed in a radiation manner in frame



FIG. 6D

Case in which there exists a larger number of motion vectors in a frame, and directions are not uniform



FIG. 6E

0982565v1 060402



FIG. 7

Macro-block in which a mosquito noise is likely to occur



FIG. 9



FIG. 10



FIG. 8A



FIG. 8B



FIG. 8C

Mode	Motion vector	Texture

FIG. 12

T00T80"Z9SS52660



FIG. 11A



FIG. 11B

OBLON, SPIVAK, ET AL
DOCKET #: 212636US2SRD
INV: Noboru YAMAGUCHI, et al.
SHEET 7 OF 7